

SPECIFICATIONS FOR 30 TON EQUIPMENT TRAILER

Vendor is to provide latest model 30 ton equipment trailer. Trailer is to utilize a pintle hook for towing.

- Trailer to be 39' in length total.
- Trailer frame to be 14" at 26 pound per foot wide flange beam.
- Trailer to have 6' tongue with tool tray and lockable lid continued frame.
- Trailer to have 5' dove tail (oak).
- Trailer to have ramp 40" wide 6' long Hydraulic Lift.
- Trailer width to be 102" total.
- Cross members to be 4" channel at 5.4 pound per foot on 16" centers.
- Deck height to be minimum 33" to a maximum 36".
- Side rails to be 8" channel with rub rail and stake pockets every 2'.
- Trailer to have treated floor (seasoned oak).
- Trailer to have checker plate over the tires.
- Trailer to have an adjustable pintle hitch (100,000 lbs capacity).
- Trailer to be equipped with a front mounted chain box.
- Trailer to be equipped with two 25,000 lbs dropleg jacks.
- Trailer to have 235 X 75R X 17.5 18 ply (new) tires.
- Trailer to be equipped with (new) bud wheels.
- Trailer to have brakes on all wheels.
- Trailer wheels to be 6.75 X 17.5 10 hole.
- Trailer to be equipped with air brakes with ABS.
- Trailer to be tri axle.
- Spring brakes on 2 axles.
- Axles to be 22,500 pound with oil both.
- Trailer to have DOT reflective tape.
- Trailer to meet all DOT and ICC specifications.
- Trailer lights to be rubber mounted.
- Trailer to be equipped with 14 total lashing/"D" rings.
- Trailer wiring to utilize 7 way plug.
- Trailer to be equipped with spray guard with anti-sail mud flaps.
- Trailer ramps are to be equipped with traction assist.
- Trailer to be equipped with spare tire and wheel.
- Trailer to be primed and painted white (minimum 2 coats).
- Vendor to provide maintenance and service manuals for each unit procured.
- Vendor to provide minimum one year warranty on all parts and labor.
- Vendor to provide Certificate of Origin and Title Application upon delivery.
- FOB destination. Delivery time may be a factor in the award of this purchase order.